

ABOUT THIS PRODUCT

Tying tape is used to bandage, wind and insulate assemblies in electrical components.



FEATURES AND BENEFITS

The tying tape is a thread structure strap, consisting of high strength rayon yarns and coated with a synthetic resin system.

The tying tape is strongly hygroscopic and be impregnated very intensively with varnishes and resins.

It is suitable for use from, thermal class B (130°C); in combination with the appropriate impregnations it is also optimally suitable for use in higher classes.

APPLICATIONS

- Bandage
- Wind and insulate assemblies in electrical components
- Tying strator windings in e-motors
- Bandaging of transformer inductors in oil or air-cooled large transformers
- Bandage of the starter inductors(starters) for the automobile industry

MATERIAL DATA

Colour: beige (nature)

Article code	Width (mm)	Thickness (mm)	Tensile strength (daN)	Elongation (threads) (%)
RTA-A-1800	ca. 1.8	min. 20	ca.9.0	1,800
RTA-6-1000	ca. 2.6	min.30	ca.9.0	1,000
RTA-8-800	ca. 3.5	min.40	ca.9.0	800
RTA-11-500	ca. 4.8	min.55	ca.9.0	500
RTA-14-400	ca. 6.1	min.70	ca.9.0	400
RTA-16-350	ca. 6.9	min.80	ca.9.0	350
RTA-18-300	ca. 7.8	min.90	ca.9.0	300
RTA-22-250	ca. 9.5	min.110	ca.9.0	250

23 Ullswater Crescent

Coulsdon

Surrey

CR5 2UY

TEL: +44(0) 20 8668 1481

WEB: www.croylek.com

EMAIL: sales@croylek.co.uk

We correspond to general request to spool these tapes with greatest possible tape length, but due to change of bobbins or unpredictable production difficulties, connections are necessary.

<Ref No v1>

TECHNICAL TABLE

Meters per spool (m)	Core-diameter (mm)	External diameter (mm)	Spool width (mm)	Weight (kg)	Spools per carton	Spools per ½ pallet	Spools per Pallet	Cartoon dimensions (mm)
1800	25	115	140	ca. 1.00	12	288	480	350 x 275 x 225
1000	25	115	140	ca. 0.90	12	288	480	350 x 275 x 225
800	25	115	140	ca. 0.90	12	288	480	350 x 275 x 225
500	25	115	140	ca. 0.80	12	288	480	350 x 275 x 225
400	25	115	140	ca. 0.85	12	288	480	350 x 275 x 225
350	25	115	140	ca. 0.85	12	288	480	350 x 275 x 225
300	25	115	140	ca. 0.80	12	288	480	350 x 275 x 225
250	25	115	140	ca. 0.85	12	288	480	350 x 275 x 225

The tying tape should be stored under normal conditions, cool., dry and protected from the light.
The goods remain capable of being processed at least 24 months provided, that they are stored properly (under normal room conditions) in their unopened bags.