

# Silicone Rubber Sleeving

## ABOUT THIS PRODUCT

Silicone rubber sleeving is well known for its high temperature resistance, flexibility and elastic characteristics. The material is post-cured to give it the added stability. The sleeving can be used for variety of industrial applications, ranging from simple fluid carrying applications to very critical environments requiring specialist materials. It is available in a number of different hardness.



### FEATURES AND BENEFITS

- High operating temperature
- Extremely flexible
- Ozone resistant
- U.V. resistant
- Fungus resistant
- Self Extinguishing
- Conforms to BS4G198 Type 4
- Conforms to BS3858 Type 5
- Conforms to Def Stan 59-15

### APPLICATIONS

- Harnessing
- Electrical insulation
- Marker sleeves
- Peristaltic pump tubing

### MATERIAL DATA

<b>Product Code</b>	<b>124</b>
<b>Material</b>	<b>Silicone</b>
<b>Standard Colour</b>	<b>Black, Red, Yellow, Green, Blue, Brown, Orange, White</b>
<b>Operating Temperature – °C</b>	<b>-60 – +180</b>
<b>Elongation at Break – %</b>	<b>250</b>
<b>Dielectric Strength – kV/mm</b>	<b>20</b>
<b>Tensile Strength – kg/cm<sup>2</sup></b>	<b>60</b>
<b>Relevant Specifications</b>	<b>Conforms to be BS4G198 Type 4</b>
	<b>Conforms to BS3858 Type 5</b>
	<b>Conforms to Def Stan 59-15</b>

## TECHNICAL TABLE

Supplied Diameter (mm)	Wall Thickness (mm)	Coil Length (m)
0.5	0.5	100m Coil
1	0.5	100m Coil
1.5	0.5	100m Coil
2	0.5	100m Coil
3	0.5	100m Coil
4	0.5	100m Coil