

SWITCHGEAR MATTING - 11KV

ABOUT THIS PRODUCT

This fine ribbed, high quality rubber matting is fully certified and tested to 11,000 volts, with a recommended safety working voltage of 450V. It has a fine ribbed, anti-slip surface pattern on one side and a cloth impression finish on the reverse, ensuring safety for operatives at lower voltage switchboard and high equipment areas.



FEATURES AND BENEFITS

- Health and safety regulation material
- Fully tested to specification
- Regulatory printing on reverse every one metre
- Good dielectric strength
- Anti-slip
- Low maintenance
- Easy to use
- Fully certified and tested to 11000 volts

APPLICATIONS

- Switchboards
- Substations
- Electrical generators
- Work benches
- Anti slip
- Electrical safety matting

MATERIAL DATA

Product Code	930
Matting Material	High quality rubber compound
Standard Colour	Black
Thickness	6mm
Hardness (Shore A)	65°
Operating Temperature – °C	-20 – + 70
Tensile Strength - Mpa	5
Elongation - %	250 (min)
Relevant Specifications	BS921/1976

TECHNICAL TABLE

Stock roll sizes (m x m x mm)	Weight (Kg/m ²)	Specifications (Compound)	Values (Typical)
10 x 0.91 x 6	6.80	Colour -	Black
10 x 1.0 x 6	6.80	Compound	SBR/NR
10 x 1.2 x 6	6.80	Hardness (shore A)	65°
		Density (SG)	1.3
		Elongation (min)	250%
		Tensile strength	5 MPA
		Abrasion resistance	180 mm ³
		Minimum temperature	-20°C
		Maximum temperature	+70°C