

UL 3271 / CSA AWM I A/B 125°C 600V


RADOX connecting leads

GENERAL PROPERTIES:

Excellent high temperature, low temperature, ozone and weathering resistance, flame retardant, easy to strip and process, heat pressure and highly abrasion resistant, soldering iron resistant, flexible.

APPLICATION:

For protected and fixed installation inside electrical equipment, especially suitable for the connection of motor windings, switchboards, magnets and transformers.



1. Conductor : Stranded tin plated copper, flexible
2. Coverage : Tape (≥ 6AWG only)
3. Insulation : RADOX
extruded irradiation crosslinked polyolefin
Colours : various

Printing:

≤ 10 mm²

AWM Style 3271 125°C 600V HUBER+SUHNER [prod.-place] RADOX CSA AWM I A/B 125°C 600V FT2 [cross section] - [part no.]-[batch no.] [prod. week]-[prod. year]

≥ 16 mm²

AWM Style 3271 125 °C 600V HUBER+SUHNER [prod.-place] RADOX CSA AWM I A/B 125°C 600V FT1, FT2 [cross section] - [part no.]-[batch no.] [prod. week]-[prod. year]

Technical data:

Voltage rating	(UL/CSA)	600	V
Testvoltage 1 min.	(UL/CSA)	2500	V
Voltage rating	(≥0.5mm ²)	600/1000	V
Testvoltage 1 min.	(≥0.5mm ²)	3500	V
Temperature rating	(UL/CSA)	+ 125	°C
Max. Temperature at short circuit	(max. 5s)	+ 280	°C
Min. temperature	flexing	- 25	°C
	fixed	- 40	°C
Min. bending radius for fixed installation	see Tab. 1		

The cables comply with the following standards:

Appliance wiring material	CSA C22.2 No. 210 ..	AWM I A/B 125°C 600 V
Appliance wiring material	UL 758	Style 3271

The cables pass the following fire tests:

Vertical flame spread FT1	(≥16mm ²)	L ≤ 250 mm, t ≤ 60 s ..	CSA C22.2 No. 2556 # 9.3
Horizontal flame spread FT2		L ≤ 100 mm	CSA C22.2 No. 2556 # 9.1
Vertical flame spread		50 < L ≤ 540 mm	EN 60332-1-2, IEC 60332-1-2
Horizontal flame spread, Appliance-Wire		V ≤ 25 mm/min.	UL 1581 # 1090

Copyright 2022 HUBER+SUHNER AG. This document may not be amended and its content is confidential. It may not be passed on to third party which are not bound by confidentiality.

The product fulfils the test and specification requirements described in this document for the stated areas of application and operating conditions. HUBER+SUHNER AG does not expressly or implicitly guarantee performance under additional or changed conditions. Deviations are to be agreed upon in writing.

HUBER+SUHNER AG
Low Frequency Division
 CH-8330 Pfäffikon
 +41 (0)44 952 22 11
 +41 (0)44 952 26 40
www.hubersuhner.com

UL 3271 / CSA AWM I A/B 125°C 600V RADOX connecting leads

Approvals:

UL
CSA

File E63322
File 069581

TABLE 1: Dimensions, weight

Cross Section: UL 758 CSA C22.2 No. 210		Cross-section: EN 60228/ IEC 60228	Conductor construction	Conductor Diameter	Core diameter D.	Weight	Bending radius	Conductor resistance at 20°C
AWG	nom. mm ²	nom. mm ²	nom. n x mm d	max. mm	mm	nom. kg / 100m	min. mm	max. Ω / km
24	0.205		19 x 0.13	0.61	2.22 ± 0.10	0.72	3 x D	86.0
22	0.324		19 x 0.16	0.77	2.40 ± 0.10	0.92	3 x D	53.1
		0.5	19 x 0.18	0.90	2.55 ± 0.10	1.0	3 x D	38.2
20	0.519		19 x 0.20	0.99	2.60 ± 0.10	1.2	3 x D	32.4
		0.75	24 x 0.20	1.13	2.80 ± 0.10	1.3	3 x D	26.7
18	0.823		19 x 0.25	1.23	2.85 ± 0.10	1.6	3 x D	20.4
		1	32 x 0.20	1.28	2.95 ± 0.10	1.6	3 x D	20.0
(16)		1.5	19 x 0.31	1.52	3.20 ± 0.10	2.1	3 x D	13.0
14	2.08		19 x 0.37	1.86	3.50 ± 0.10	2.9	3 x D	9.32
		2.5	48 x 0.25	2.06	3.75 ± 0.10	3.2	3 x D	8.21
12	3.31		37 x 0.35	2.35	4.00 ± 0.15	4.2	3 x D	5.88
		4	56 x 0.30	2.64	4.35 ± 0.15	4.9	3 x D	5.09
10	5.26		37 x 0.44	3.02	4.70 ± 0.15	6.4	3 x D	3.62
		6	84 x 0.30	2.98	4.70 ± 0.15	6.9	3 x D	3.23
(8)		10	80 x 0.40	3.94	6.40 ± 0.15	12.1	3 x D	1.95
(6)		16	119 x 0.40	5.4	8.60 ± 0.2	18.8	3 x D	1.24
(4)		25	182 x 0.40	6.7	9.90 ± 0.2	26.8	3 x D	0.795
(2)		35	266 x 0.40	7.9	11.1 ± 0.2	36.4	3 x D	0.565
(1)		50	378 x 0.40	9.4	13.7 ± 0.25	54.3	4 x D	0.393
(2/0)		70	348 x 0.49	11.5	15.8 ± 0.25	70.1	4 x D	0.273
(3/0)		95	456 x 0.49	13.0	17.5 ± 0.3	90.2	4 x D	0.207
(4/0)		120	570 x 0.50	14.7	19.6 ± 0.3	114	4 x D	0.164
(250kcmil)		150	722 x 0.49	16.2	20.9 ± 0.3	139	4 x D	0.132